

Eaton 9PX 2200i RT2U - UPS (rack-mountable / external)

AC 200/208/220/230/240 V - 2200 Watt - 2200 VA - 1-phase - RS-232 - USB - Ethernet 10/100/1000 - output connectors: 10 - PFC - 2U

Group	Power Supply
Manufacturer	Eaton
Manufacturer item no.	9PX2200IRTN



Description

The Eaton 9PX UPS provides energy-efficient power protection for small & medium Datacenters, IT rooms and Infrastructure. Delivering double conversion protection with 40% less energy usage and 28% more power 9PX is the perfect UPS for IT and Facility managers that are concerned by energy cost and are looking for next generation power protection solutions.

Main features

Product Description	Eaton 9PX 2200i RT2U - UPS - 2200 Watt - 2200 VA
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Rack Size	2U
Weight	25 kg
Input Wiring	1-phase
Input Voltage	AC 200/208/220/230/240 V
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	2200 Watt / 2200 VA
Input Connectors	1
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19 16A
Networking	RS-232, USB, Ethernet 10/100/1000
Dimensions (WxDxH)	44 cm x 60.5 cm x 8.65 cm
Environmental Standards	ENERGY STAR

Extended details

	General
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Height (Rack Units)	2U
	Power Device
UPS Technology	On-line
Input Voltage	AC 200/208/220/230/240 V
Input Voltage Range	AC 176 - 276 V
Input Wiring	1-phase

Frequency Required	40 - 70 Hz
Input Connectors	1
Power Output Connectors Details	8 x power IEC 60320 C13 2 x power IEC 60320 C19 16A
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	2200 Watt / 2200 VA
Efficiency	98%
	Battery
Run Time (Up To)	44 min at 300 Watts 23 min at 500 Watts 15 min at 800 Watts 9 min at 1200 Watts 5 min at 1800 Watts
	Networking
Remote Management Interface	RS-232, USB, Ethernet 10/100/1000
	Expansion / Connectivity
Interfaces	1 x management (USB) 1 x management (RS-232) 1 x management (Gigabit Ethernet) - RJ-45
Expansion Slots	1 (total) / 0 (free) x Expansion Slot
	Miscellaneous
Features	LCD display, internal bypass
Compliant Standards	FCC Class B certified, TUV, CISPR 22 Class B, UL 1778, CB, IEC 62040-2, cULus, CSA 22.2, KC, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
	Software / System Requirements
Software Included	Intelligent Power Software Suite
	Environmental Standards
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Sound Emission	40 dB
	Dimensions & Weight
Width	44 cm
Depth	60.5 cm
Height	8.65 cm
Weight	25 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.