

TP-LINK Archer T2U - Network adapter

USB 2.0 - 802.11ac

Group	Interface Cards
Manufacturer	TP-LINK
Manufacturer item no.	ARCHER T2U
EAN/UPC	6935364050856



Description

TP-LINK's Archer T2U comes with the next generation Wi-Fi standard - 802.11ac, 3 times faster than wireless N speeds. With 433 Mbps wireless speeds over the crystal clear 5 GHz band or 150 Mbps over the 2.4 GHz band, the Archer T2U is the superior choice for seamless HD streaming, online gaming and other bandwidth-intensive tasks. TP-LINK's Archer T2U is a dual band USB Adapter that provides selectable 5 GHz and 2.4 GHz bands for the latest standard and backward compatibility to existing Wi-Fi network. It gives users the ability to access crystal clear 5 GHz connections to upgrade their notebook or PC's wireless capabilities, while ensuring that they can still access legacy 2.4 GHz band wireless networks.

Main features

Product Description	TP-Link Archer T2U - network adapter - USB 2.0
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB 2.0
Dimensions (WxDxH)	4.1 cm x 1.95 cm x 0.87 cm
Data Link Protocol	802.11ac
Data Transfer Rate	600 Mbps
Frequency Band	2.4 GHz, 5 GHz
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.1x, IEEE 802.11n, IEEE 802.11ac
System Requirements	Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Windows 8 (32/64 bits)

Extended details

General	
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB 2.0
Networking	
Connectivity Technology	Wireless
Data Link Protocol	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Data Transfer Rate	600 Mbps
Line Coding Format	DBPSK, DQPSK, CCK, 64 QAM, 256 QAM, 16 QAM, OFDM

Frequency Band	2.4 GHz, 5 GHz
Features	Ad-Hoc Mode, Wi-Fi Protected Setup (WPS)
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.1x, IEEE 802.11n, IEEE 802.11ac
Aerial	
Antenna	Internal
Directivity	Omni-directional
Miscellaneous	
Encryption Algorithm	128-bit WEP, 64-bit WEP, WPA-PSK, WPA2-PSK
Compliant Standards	FCC, RoHS
Software / System Requirements	
Software Included	Drivers & Utilities
OS Required	Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Windows 8 (32/64 bits)
Dimensions & Weight	
Width	4.1 cm
Depth	1.95 cm
Height	0.87 cm
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.