



Dymo LabelWriter 5XL - Label printer

direct thermal - Roll (11.5 cm) - 300 dpi - up to 53 labels/min - USB 2.0 - LAN

Group	Printers
Manufacturer	Dymo
Manufacturer item no.	2112725
EAN/UPC	3026981127250

Description

The DYMO LabelWriter 5XL label printer is the ideal choice for eCommerce sellers, printing 4" x 6" shipping labels for UPS, FedEx, USPS directly from eBay, Amazon, and many others with free DYMO software via USB or LAN network connectivity. With unique Automatic Label Recognition, you always know the size, type, and number of labels remaining. The direct thermal printer cuts the cost of ink and toner.

Main features

Product Description	DYMO LabelWriter 5XL - label printer - B/W - direct thermal
Printer Type	Label printer - direct thermal - B/W
Weight	885 g
Max Media Size	Roll (11.5 cm)
Print Speed	Up to 53 labels/min - B/W
Max Resolution (B&W)	300 dpi
Interface	USB 2.0, LAN
Media Type	Labels, thermal paper
Power	AC 100-240 V
System Requirements	Windows 8.1 or later, Apple macOS 10.13 or later
Dimensions (WxDxH)	18 cm x 18.7 cm x 13.6 cm

Extended details

General

Printer Type	Label printer - direct thermal - monochrome
--------------	---

Printer

Print Speed	Up to 53 labels/min - B/W
Connectivity Technology	Wired
Interface	USB 2.0, LAN
Max Resolution (B&W)	300 dpi

Media Handling	
Media Type	Labels, thermal paper
Max Media Size	Roll (11.5 cm)
Media Sizes	Roll (11.5 cm)
Max Printing Width	105.73 mm
Media Feeders	1 x manual - 1 roll - Roll (11.5 cm)
RFID	
Frequency	13.56 MHz
Expansion / Connectivity	
Connections	1 x USB 2.0 - 4 pin USB Type B 1 x LAN - RJ-45
Miscellaneous	
Cables Included	1 x USB cable
Compliant Standards	GS, NOM, FCC, ANATEL, S Mark, RCM, BIS, COFETEL, Subtel, CNC, CRT
Power	
Power Device	Power adapter - external
Voltage Required	AC 100-240 V
Frequency Required	50/60 Hz
Software / System Requirements	
OS Required	Windows 8.1 or later, Apple macOS 10.13 or later
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	4 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 95%
Dimensions & Weight	
Width	18 cm
Depth	18.7 cm
Height	13.6 cm
Weight	885 g