

ASUS ProArt PA278QV - LED monitor

27" - 2560 x 1440 WQHD @ 75 Hz - IPS - 350 cd/m² - 1000:1 - 5 ms
 - HDMI - DVI-D - DisplayPort - Mini DisplayPort - speakers - black

Group	Flat Screens
Manufacturer	ASUS
Manufacturer item no.	90LM05L1-B01370
EAN/UPC	4718017603614



Description

ProArt display PA278QV is a 27-inch monitor designed to satisfy the needs of creative professionals, from photo and video editing to graphic design. ProArt display PA278QV is factory calibrated and Calman Verified to deliver superb color accuracy ($\Delta E < 2$). It also provides industry-standard 100% sRGB/100% Rec. 709 color space coverage. With ASUS-exclusive features, such as ProArt Preset and ProArt Palette with six-axis color, black-level and brightness adjustments, PA278QV makes it easy to achieve the exact look you desire quickly, easily and precisely.

Main features

Product Description	ASUS ProArt PA278QV - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class E
Features	USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440 at 75 Hz
Pixel Pitch	0.2331 mm
Brightness	350 cd/m ²
Contrast Ratio	1000:1 / 100000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Colour Support	16.7 million colours
Colour Gamut	100% sRGB
Input Connectors	HDMI, DVI-D, DisplayPort, Mini DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black

Dimensions (WxDxH) - with stand	61.5 cm x 22.6 cm x 38.2 cm
Weight	7.56 kg
Environmental Standards	ENERGY STAR Qualified
Compliant Standards	UL, TUV GS, VCCI, BSMI, cUL, CB, CCC, TUV Ergo, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, MEPS, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CEL, RCM, TUV Rheinland Low Blue Light Certification, CU, TUV Rheinland Flicker Free Certification

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440 at 75 Hz
Pixel Pitch	0.2331 mm
Brightness	350 cd/m ²
Contrast Ratio	1000:1 / 100000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	100% sRGB
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	46 - 75 Hz
Horizontal Refresh Rate	30 - 112 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	HDCP, Trace Free Technology, ASUS Smart Contrast Ratio (ASCR), ASUS QuickFit Virtual Scale, Flicker Free technology, Adaptive-Sync technology, Colour Temperature Selection, 6-Axis Color Adjustments, Low Blue Light technology, CalMAN Verified, ProArt Preset, ProArt Palette, Delta E=2 colour accuracy
Colour	Black
Dimensions	61.5 cm x 22.6 cm x 38.2 cm - with stand

Weight	7.56 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	DVI-D (dual link) (HDCP) Headphones DisplayPort 1.2 HDMI 4 x USB-C 3.2 Gen 1 downstream USB-C 3.2 Gen 1 upstream (Type B) Mini DisplayPort Audio line-in
	Mechanical
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	180
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Cables Included	1 x DisplayPort cable 1 x Mini DisplayPort-DisplayPort cable 1 x HDMI cable 1 x USB-A to USB-B cable
Compliant Standards	UL, TUV GS, VCCI, BSMI, cUL, CB, CCC, TUV Ergo, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, MEPS, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CEL, RCM, TUV Rheinland Low Blue Light Certification, CU, TUV Rheinland Flicker Free Certification
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	22 kWh/1000h
Power Consumption (Typical)	12.5 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0 Watt
	Dimensions & Weight
Dimensions & Weight Details	Without stand - width: 61.5 cm - depth: 5.1 cm - height: 37.2 cm - weight: 4.83 kg With stand - width: 61.5 cm - depth: 22.6 cm - height: 38.2 cm - weight: 7.56 kg
	Dimensions & Weight (Shipping)

Shipping Depth	21.6 cm
Shipping Height	46.4 cm
Shipping Weight	10.74 kg
Sustainability Information	
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © 1WorldSync. Subject to technical modifications and errors.