



APC Smart-UPS 1500VA LCD RM - UPS (rack-mountable)

AC 230 V - 1000 Watt - 1500 VA - Ethernet - RS-232 - USB - output connectors:
4 - 2U - black - with APC UPS Network Management Card - for P/N:
AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432
- NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1500RMI2UNC
EAN/UPC	0731304327684

Description

Intuitive LCD interface provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys.

Predictive replace battery date dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.

Main features

Product Description	APC Smart-UPS 1500VA LCD RM - UPS - 1000 Watt - 1500 VA - with APC UPS Network Management Card
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	28.58 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	1000 Watt / 1500 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	Power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	7 min at full load
Networking	Ethernet, RS-232, USB
Included Accessories	Rack mounting rails, temperature probe
Colour	Black
Dimensions (WxDxH)	43.2 cm x 45.7 cm x 8.9 cm
Bundled with	APC UPS Network Management Card
Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3150W, AR3155SP, AR3155W, AR3300W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC UPS Network Management Card

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Required	50 Hz $\pm$ 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	Power IEC 60320 C13
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	1000 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker

Battery

Technology	Lead Acid
Run Time (Up To)	7 min at full load 26 min at half load
Recharge Time	3 hours
Transfer Time	2 ms
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	Ethernet, RS-232, USB
-----------------------------	-----------------------

Expansion / Connectivity

Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB) - 4 pin USB Type B Management (USB) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot

Miscellaneous

Included Accessories	Rack mounting rails, temperature probe
Cables Included	Serial cable - external USB cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Software / System Requirements

Software Included	APC PowerChute Business Edition
-------------------	---------------------------------



Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
-------------------	---

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA

Dimensions & Weight

Width	43.2 cm
Depth	45.7 cm
Height	8.9 cm
Weight	28.58 kg

Dimensions & Weight (Shipping)

Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.84 kg

Compatibility Information

Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF202BLK, ACF400, ACF402, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR201, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, NBPD0180, NBRK0201, NBRK0320, NBRK0320E, NBRK0551, NBWL0355, NBWL0356A
--------------	---



Technical data © CNET Content Solutions. Subject to technical modifications and errors.