



APC Smart-UPS 3000VA LCD RM - UPS (rack-mountable)

AC 230 V - 2700 Watt - 3000 VA - Ethernet - RS-232 - USB - output connectors: 9 - 2U - black - with APC UPS Network Management Card - for P/N: AR3105W - AR3140G - AR3155W - AR3305W - AR3340G - AR3355W - AR4038IX432 - NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT3000RMI2UNC
EAN/UPC	0731304327707

Description

APC Smart-UPS protects your data by supplying reliable, network-grade power in either traditional Tower or Rack-optimized form factors for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical file servers (Intel or UNIX based), minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs. Rack Mount versions are the choice for rack optimized servers, server appliances, blade servers, other blade devices and rack-mounted network switches and hubs.

Main features

Product Description	APC Smart-UPS 3000VA LCD RM - UPS - 2700 Watt - 3000 VA - with APC UPS Network Management Card
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	44.19 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	2700 Watt / 3000 VA
Input Connectors	1
Output connectors	8 x power IEC 60320 C13 1 x power IEC 60320 C19
Battery	Lead Acid
Run Time (Up To)	3.2 min at full load
Networking	Ethernet, RS-232, USB
Included Accessories	Rack mounting rails, temperature probe
Colour	Black
Dimensions (WxDxH)	48 cm x 68.3 cm x 8.6 cm
Bundled with	APC UPS Network Management Card
Designed For	P/N: AR2200, AR2280, AR2487G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W,



AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP,
AR4038IX432, NBPD0180, NBWL0356A

Extended details

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC UPS Network Management Card

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	47 - 63 Hz
Frequency Required	50/60 Hz $\pm$ 3Hz
Input Connectors	1
Power Output Connectors Details	8 x power IEC 60320 C13 1 x power IEC 60320 C19
Output Voltage	AC 230 V $\pm$ 5% - 47 - 63 Hz
Power Capacity	2700 Watt / 3000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	320 Joules
Circuit Protection	Circuit breaker

Battery

Technology	Lead Acid
Run Time (Up To)	3.2 min at full load 11.5 min at half load
Recharge Time	3 hours
Transfer Time	4 ms
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	Ethernet, RS-232, USB
-----------------------------	-----------------------

Expansion / Connectivity

Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB) - 4 pin USB Type B Management (Ethernet) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot

Miscellaneous

Included Accessories	Rack mounting rails, temperature probe
Cables Included	Serial cable - external USB cable - external Power cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	GS, VDE, IEC 62040-2, IRAM, RoHS, WEEE, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Software / System Requirements

Software Included	APC PowerChute Business Edition
-------------------	---------------------------------

Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
-------------------	---

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	55 dBA

Dimensions & Weight

Width	48 cm
Depth	68.3 cm
Height	8.6 cm
Weight	44.19 kg

Dimensions & Weight (Shipping)

Shipping Width	60 cm
Shipping Depth	98 cm
Shipping Height	25.4 cm
Shipping Weight	51.59 kg

Compatibility Information

Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF202BLK, ACF400, ACF402, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR201, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, NBP0180, NBRK0201, NBRK0320, NBRK0320E, NBRK0551, NBWL0355, NBWL0356A
--------------	---