

D-Link DGS 1005P - Switch - 5 x 10/100/1000 (4 PoE+)

desktop - PoE+ (60 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1005P/E
EAN/UPC	0790069440984



Description

The D-Link DGS-1005P 5-Port Desktop Gigabit PoE+ Switch enables you to connect Power over Ethernet (PoE) devices such as wireless access points (APs), network video cameras and IP phones to the network. Built with home and small business users in mind, the DGS-1005P is compact and operates silently, making it ideal for most rooms and offices.

Main features

Product Description	D-Link DGS 1005P - switch - 5 ports
Device Type	Switch - 5 ports
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000 (4 PoE+)
Power Over Ethernet (PoE)	PoE+
PoE Budget	60 W
Performance	Switching fabric speed: 10 Gbps Forwarding rate: 7.44 Mpps
MAC Address Table Size	2K entries
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, fanless, 64KB packet buffer, SOHO (Small Office/Home Office), Energy-Efficient Ethernet (EEE)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Dimensions (WxDxH)	10 cm x 9.8 cm x 2.8 cm
Weight	260 g

Extended details

General	
Device Type	Switch - 5 ports
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000 (4 PoE+)
Power Over Ethernet (PoE)	PoE+

PoE Budget	60 W
Performance	Switching fabric speed: 10 Gbps Forwarding rate: 7.44 Mpps
MAC Address Table Size	2K entries
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, fanless, 64KB packet buffer, SOHO (Small Office/Home Office), Energy-Efficient Ethernet (EEE)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Status Indicators	Power, status, PoE, link/activity/speed
Expansion / Connectivity	
Interfaces	5 x 1000Base-T RJ-45 4 ports (PoE+) - 30 W
Power	
Power Device	External power adapter
Power Consumption Operational	64.5 Watt
Power Consumption Stand by	0.54 Watt
Miscellaneous	
Compliant Standards	Plug and Play, VCCI, BSMI, cUL, CB, FCC, LVD, RCM
Dimensions & Weight	
Width	10 cm
Depth	9.8 cm
Height	2.8 cm
Weight	260 g
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	0 - 95% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.