



TP-LINK Archer T2U Nano - Network adapter

USB 2.0 - 802.11ac

Group	Interface Cards
Manufacturer	TP-LINK
Manufacturer item no.	ARCHER T2U NANO
EAN/UPC	6935364099978

Description

The Archer T2U Nano receives Wi-Fi signals on two separate bands. Supporting 256QAM technology increases 2.4 GHz data rate from 150 Mbps to 200 Mbps for 33% faster performance. 433 Mbps on 5 GHz is ideal for HD video streaming and lag-free online gaming, while 200 Mbps on 2.4 GHz is perfect for normal use such as web surfing with legacy devices.

Main features

Product Description	TP-Link Archer T2U Nano - network adapter - USB 2.0
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB 2.0
Dimensions (WxDxH)	1.5 cm x 1.86 cm x 0.7 cm
Data Link Protocol	802.11ac
Data Transfer Rate	600 Mbps
Frequency Band	2.4 GHz, 5 GHz
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.1x, IEEE 802.11n, IEEE 802.11ac
System Requirements	Microsoft Windows XP/ 7 / 8 / 8.1 / 10, Apple MacOS X 10.9 - 10.13

Extended details

General	
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB 2.0
Networking	
Connectivity Technology	Wireless
Data Link Protocol	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Data Transfer Rate	600 Mbps



Line Coding Format	DBPSK, DQPSK, CCK, 64 QAM, 256 QAM, 16 QAM
Frequency Band	2.4 GHz, 5 GHz
Features	Ad-Hoc Mode
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.1x, IEEE 802.11n, IEEE 802.11ac
Aerial	
Antenna	Internal
Directivity	Omni-directional
Miscellaneous	
Encryption Algorithm	128-bit WEP, 64-bit WEP, WPA, WPA2, WPA-PSK, WPA2-PSK
Compliant Standards	FCC, RoHS
Software / System Requirements	
Software Included	Drivers & Utilities
OS Required	Microsoft Windows XP/ 7 / 8 / 8.1 / 10, Apple MacOS X 10.9 - 10.13
Dimensions & Weight	
Width	1.5 cm
Depth	1.86 cm
Height	0.7 cm
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.